



The L1A2 detonator is designed to be initiated with safety fuze.

It comprises an aluminium tube with an output charge of PETN initiated with a primary charge of Aluminium/ Lead Styphnate/ Lead Azide. Each detonator is fitted with a waterproof rubber cap.

Detonators are packed in a compact, black, conducting, plastic, rigid wallet ideal for carrying in field operations.

The L1A2 Non-Electric Detonator is in service with the UK MoD and is supplied in a full military IM pack.



Technical Details

Tube Diameter (mm)	6.4
Length (mm)	59
Charge Weight (g)	1.1 max PETN
Shelf Life (yrs)	5

References

Product Code	L1A2
NATO Stock Number	1375-99-577-1644
Hazard Class	1.4S
UN Number	0455
Proper Shipping Name	DETONATORS, NON-ELECTRIC for blasting

Shipping (in approved packaging)

Outer Pack	H83 Steel Box
Inner Pack	Plastic Wallet
Quantity per Inner Pack	2
Quantity per Outer Pack	24 (12 inners)
NEQ (kg) per 24	0.035
Gross Weight (kg)	7.1
Dimension (cm)	30 x 16 x 19

Chemring Energetics UK Ltd

Ardeer Site, Stevenston, Ayrshire, KA20 3LN, UK
Tel: 01294 487007 | Email: info@chemringenergetics.co.uk

Registered Office: Ardeer Site, Stevenston, Ayrshire, KA20 3LN

Approved to ISO 9001 | Part of the Chemring Group

©This document is copyright and is wholly proprietary owned by Chemring Energetics UK Limited - July 24

Issue 02

For more information visit:

www.chemring.com/chemring-energetics-uk

The information in this datasheet should not be used as a technical specification, for engineering calculations, or for system design and integration. It is provided in good faith and is subject to change without notification. It is for the customer and/ or System Design Authority to satisfy themselves of the safety and suitability for its own particular purpose