



This device is designed to provide a means of ignition from an electrically ignited fusehead to a pyrotechnic fuse of specific diameter.

Supplied in full military pack the igniter consists of a military E Type fusehead crimped into a copper tube with a vent hole in the side.

The tube has an integral stop to ensure correct fitting to safety fuze.

The wires are twisted to reduce the risk of accidental initiation by stray Radio Frequency (RF) interference



## Technical Details

Body Length (mm)	34
Body Diameter (mm)	6
Wire Gauge (swg)	23 (0.5mm)
Wire Length (mm)	380
Resistance (Ohms)	0.9—1.6
All Fire Current (Amps)      10ms Pulse	0.55
No Fire Current (Amps)	0.3
Storage Life (yrs)	5

## References

Product Code	ISFE
NATO Stock Number	1375-99-942-3348
Hazard Class	1.4S
UN Number	0131
Proper Shipping Name	LIGHTERS, FUSE

## Shipping Information (in approved packaging)

Outer Pack	H83 Steel Box
Dimensions (mm)	300 x 160 x 190
Quantity per Pack	500
NEQ (kg)	0.02
Gross Weight (kg)	6.5

### Chemring Energetics UK Ltd

Ardeer Site, Stevenston, Ayrshire, KA20 3LN, UK  
**Tel:** 01294 487007 | **Email:** info@chemringenergetics.co.uk

Registered Office: Ardeer Site, Stevenston, Ayrshire, KA20 3LN

Approved to ISO 9001 | Part of the Chemring Group

©This document is copyright and is wholly proprietary owned by Chemring Energetics UK Limited - August 24

Issue 02

For more information visit:

[www.chemring.com/chemring-energetics-uk](http://www.chemring.com/chemring-energetics-uk)

The information in this datasheet should not be used as a technical specification, for engineering calculations, or for system design and integration. It is provided in good faith and is subject to change without notification. It is for the customer and/ or System Design Authority to satisfy themselves of the safety and suitability for its own particular purpose