



Safety Fuze is used in demolition work where a delay is required to give personnel time to retire to a place of safety before the charge detonates.

Application

Safety Fuze is often used in conjunction with an L1A2 Non-Electric Detonator crimped onto one end of the Safety Fuze which in turn is placed into the main charge. The other end is initiated via Match Fuzee or a Grip Switch fitted with a Flash Initiator.

Description

Safety Fuze consists of a train of gunpowder enclosed in a yarn wrapped in waterproof black outer polyethylene covering with a nominal diameter of 5.1mm.

Supplied in 8 meter lengths coiled and fitted with a reusable rubber seal on each end, sealed in a bag. 10 off coils are packaged in an H83 container.

Safety Fuze burns at 131 +/- 13 seconds per metre (or 7.5mm per second) allowing the user to accurately calculate the length of Safety Fuze required to provide the desired delay.

Technical Details

Burning Speed(secs/m)	131 +/- 13
Explosive Type	Black Powder
Explosive Quantity (g/m)	5.6
Storage Life (yrs)	5

References

Product Code	Safety Fuze
NATO Stock Number	1375-99-248-4203
Hazard Class	1.4S
UN Number	0105
Proper Shipping Name	FUSE, SAFETY

Shipping Information (in approved packaging)

Outer Pack	H83 Steel Box
Dimensions (mm)	300 x 160 x 190
Quantity per Pack	80m
NEQ (kg)	0.488
Gross Weight (kg)	5

Chemring Energetics UK Ltd

Ardeer Site, Stevenston, Ayrshire, KA20 3LN, UK
Tel: 01294 487007 | **Email:** info@chemringenergetics.co.uk

Registered Office: Ardeer Site, Stevenston, Ayrshire, KA20 3LN

Approved to ISO 9001 | Part of the Chemring Group

©This document is copyright and is wholly proprietary owned by Chemring

Energetics UK Limited - August 24

Issue 02

For more information visit:

www.chemring.com/chemring-energetics-uk

The information in this datasheet should not be used as a technical specification, for engineering calculations, or for system design and integration. It is provided in good faith and is subject to change without notification. It is for the customer and/ or System Design Authority to satisfy themselves of the safety and suitability for its own particular purpose