

RE70 M3 Plus

A modular recoilless disruptor and de-armer



a range of fluid and frangible projectiles.

The RE70 M3 Plus can be deployed either close up to the target UXB, ED or IED in the conventional way or, with a significant stand off from the target. The purpose of the stand off capability is to lower the threshold of danger to a bomb technician who is manually placing the de armer disruptor, or a robotic vehicle carrying it.

When deployed with a stand off, the RE70 M3 Plus is used in conjunction with an elastomer projectile or a spin stabilised frangible projectile in the disruptor role or, with a spin stabilised plain slug projectile in the dearmer role. The tool is powered by a range of electrically initiated 0.5 calibre power cartridges: super high gas, high velocity and medium velocity. The system fires projectiles with a mass of up to 290 g (10 oz).

The RE70 M3 Plus combines recoilless operation, with accuracy and ease of deployment. The totally balanced annular compensator system is a key feature eliminating recoil, enhancing accuracy and enabling the tool to be considerably lighter than conventional disruptors which require heavy mass to reduce recoil. The feature of recoilless operation also makes the equipment user friendly and eliminates the danger of collateral damage from recoil. These benefits mean that the system can even be fitted to small robots with a mass of only 25-30kg.

RE70 M3 Plus

| Parameter | Value | |
|-------------------------------|--------------------|--|
| Disruptor with muzzle | 3.85 kg | |
| (unloaded) | | |
| Disruptor with choke | 3.5 kg | |
| (unloaded) | | |
| Multi-position stand with | 4.6 kg | |
| mounting block | | |
| Disruptor mounted on multi- | 9 kg | |
| position stand with laser and | | |
| telescopic sights | | |
| Disruptor loaded and ready | 10 kg | |
| for placement | | |
| Complete kit in transit case | 26 kg | |
| including stand | | |
| Transit case | 620 x 490 x 215 mm | |
| Disruptor length with | 475 mm | |
| choke fitted | | |
| Disruptor length with | 540 mm | |
| muzzle brake | | |
| Overall diameter across | 76 mm | |
| compensator | | |

RE70 M3 PLUS FEATURES

Breech Module

Compensator

• Breech Plug Assembly

Capture Gate

Short Barrel (I" bore)

Barrel 40 mm

Muzzle 40 mm

Choke Barrel

Compensator Tool Loading •

AFP Loading Adaptor

Projectile Tool Loading

AFF LOading Adaptor

 Tool Pouch (containing Universal Rod, Cleaning Brushes (x3), Universal Spanner, Allen Key Set, Breech Contact Cleaning Probe, Laser Key)

Telescopic Sight (long eye relief and adjustable to x 4)

• 2 x Laser Sight/Zeroing Aid

• Lightweight Multi-position Stand and Mounting Block



ORDERING

| Description | Stock Number | NSN |
|------------------|--------------|------------------|
| RE70 M3 Plus Kit | 800-0911 | 1385-99-134-3601 |

Chemring Technology Solutions Ltd

Roke Manor, Old Salisbury Lane, Romsey, Hampshire, SO51 0ZN, UK

T: +44 (0)1794 833000 • F: +44 (0)1794 833433

www.chemringts.com • info@chemringts.com

© Chemring Technology Solutions Limited 2016. All rights reserved. This publication is issued to provide outline information only, which (unless agreed by the company in writing) may not be used, applied or reproduced for any purpose or form part of any order or contract or be regarded as representation relating to the products or services concerned. The company reserves any right to alter without notice the specification, design, or conditions of supply of any product or service. This is a published work the copyright in which vests in Chemring Technology Solutions Limited.